DATASHEET - Z-HK



Auxiliary contact, 1N/O+1N/C, 8 A, 250 V AC

Part no.	**Z-HK** **248432**
EL Number (Norway)	**1609487**

General specifications

Product name	Eaton Distribution parts
Part no.	Z-HK
EAN	4015082484323
Product Length/Depth	80 millimetre
Product height	65.5 millimetre
Product width	8.8 millimetre
Product weight	0.04 kilogram
Compliances	RoHS conform
Certifications	IEC 61373 EN45545-2
Product Tradename	None
Product Type	Distribution parts
Product Sub Type	None
Public Consumption	Yes
PDH Status	Active
Product Family Description	ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable	Yes

Product Specification Details

Accessory/spare part type	Auxiliary contacts
Additional equipment required	Auxiliary switch
Ambient operating temperature - max	40 °C
Ambient operating temperature - min	-5 °C
Application	Switchgear for industrial and advanced commercial applications
Assembly width	0.5
Device fitting	Earth leakage switch
EL number	1609487
Functions	Auxiliary switch
Mounting method	For fitting on left to: FI
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	1
Number of contacts (normally open contacts)	1
Number of poles at main contact unit - max	2
Number of switches (fault signal)	0
Rated operational voltage (Ue) - max	230 V
Rated switch current	3 A
Suitable for current of main contact unit - max	8 A
Type	Accessory for residual current circuit breaker Accessory
Used with	Accessory Accessory for residual current circuit breaker Auxiliary contacts
Voltage type	AC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)

Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])

Device fitting	Earth leakage switch
Function	Auxiliary switch

Width in number of modular spacings			0.5
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	3
Rated voltage		V	230
Voltage type			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			2
Suitable for max. current main contact unit		A	8

© 04/2023 by Eaton Industries GmbH