

DATASHEET - CYLINDRICAL FUSE 10 X 38 0-5A GG 500V AC



Fuse-link, LV, AC 500 V, 10 x 38 mm, gL/gG, IEC

Part no. CYLINDRICAL FUSE 10 x 38 0-5A GG 500V AC
C10G0.5
EL Number 1600203
(Norway)

Similar to illustration

General specifications		
Product name		Eaton Bussmann series low voltage cylindrical fuse
Part no.		CYLINDRICAL FUSE 10 x 38 0-5A GG 500V AC
EAN		5027590493376
Product Length/Depth		38 millimetre
Product height		10 millimetre
Product width		10 millimetre
Product weight		7.7 gram
Compliances		CE Marked RoHS Compliant
Certifications		IEC 60269
Product Tradename		None
Product Type		Low voltage cylindrical fuse
Product Sub Type		None
Electrical data		
Amperage Rating		0.5 A
Voltage rating		500 V
Voltage type		AC
Breaking capacity		120 kA
Utilization category		gG (cable protection/equipment protection)
Compatible fuse holder		
Suitable for		CHM Modular fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])		
Model		Ceramic fuse
Size		10x38 mm
Voltage type		AC
Rated current	A	0.5
Rated voltage	V	500
Utilization category		gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	120
Power loss at rated current	W	1.43