

DATASHEET - CYLINDRICAL FUSE 10 X 38 1A GG 500V AC



Fuse-link, LV, 1 A, AC 500 V, 10 x 38 mm, gL/gG, IEC

Part no. CYLINDRICAL FUSE 10 x 38 1A GG 500V AC
C10G1
EL Number 1600252
(Norway)

General specifications			
Product name			Eaton Bussmann series low voltage cylindrical fuse
Part no.			CYLINDRICAL FUSE 10 x 38 1A GG 500V AC
EAN			5027590493383
Product Length/Depth			38 millimetre
Product height			10 millimetre
Product width			10 millimetre
Product weight			8.2 gram
Compliances			GoST-R RoHS Compliant CE Marked
Certifications			IEC 60269
Product Tradename			None
Product Type			Low voltage cylindrical fuse
Product Sub Type			None
Electrical data			
Amperage Rating			1 A
Voltage rating			500 V
Voltage type			AC
Breaking capacity			120 kA
Utilization category			gG (cable protection/equipment protection)
Compatible fuse holder			
Suitable for			CHM Modular fuse holder

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecI@ss13-27-14-20-02 [AFZ797018])		
Model		Ceramic fuse
Size		10x38 mm
Voltage type		AC
Rated current	A	1
Rated voltage	V	500
Utilization category		gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	120
Power loss at rated current	W	2.77