

Eaton 216867

Catalog Number: 216867

Eaton Moeller® series M22 Selector switch, RMQ-Titan, With thumb-grip, maintained, 2 positions, Bezel: titanium

General specifications



Product Name	Catalog Number
Eaton Moeller® series M22 Selector switch	216867
	Model Code
	M22-WRK
EAN	Product Length/Depth
4015082168674	46 mm
Product Height	Product Width
30 mm	30 mm
Product Weight	Compliances
0.013 kg	CE Marked

Certifications

IEC 60947-5

CSA Std. C22.2 No. 94-91

CSA Std. C22.2 No. 14-05

EN 60947-5

UL 508

VDE

CSA Class No.: 3211-03

UL Category Control No.: NKCR

CSA-C22.2 No. 94-91

IEC/EN 60947

CE

UL

CSA

UL File No.: E29184

CSA File No.: 012528

CSA-C22.2 No. 14-05

IEC/EN 60947-5

Product specifications

Type

Selector switch actuator

Actuator color

Black

Actuator function

Maintained

Switching function latching

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

Resources

Catalogs

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

[Flip catalog - Product Range Catalog - Command and indication](#)

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

Certification reports

[0000SPC-183](#)

[0000SPC-179](#)

Declarations of conformity

[DA-DC-00004135.pdf](#)

[DA-DC-00004157.pdf](#)

Drawings

[116X196](#)

[eaton-operating-switch-m22-dimensions.eps](#)

[116X115](#)

[eaton-operating-switch-m22-dimensions-002.eps](#)

Drawings

[eaton-operating-switch-m22-changeover-switch-3d-drawing-002.eps](#)

[eaton-general-m22-symbol.eps](#)

[eaton-general-m22-standards.eps](#)

[116I266](#)

[0000SPC-180](#)

[eaton-general-approval-m22-symbol.eps](#)

eCAD model

[ETN.M22-WRK](#)

[ETN.216867.edz](#)

Installation instructions

[IL04716002Z](#)

Installation videos

[RMQ Flat Design](#)

mCAD model

[DA-CS-wahltaste_knebel](#)

[eaton-cadenas-side_view-wahltaste_knebel_side.pra](#)

[DA-CD-wahltaste_knebel](#)

[eaton-cadenas-path-temp-wahltaste_knebel.3db](#)

[eaton-cadenas-front_view-wahltaste_knebel_front.pra](#)

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Fitted with:

Front ring

Operating frequency

2000 Operations/h

Pollution degree

3

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Connection to SmartWire-DT

With SWD-RMQ connections

Yes

Actuator type

Toggle

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

Multimedia

[easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)

[MCI Multicolor Light Indicator M22 with SmartWire-DT](#)

[RMQ small E-Stop emergency-stop button](#)

[MCI MultiColor Light Indicator RMQ compact solution](#)

Sales notes

[eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf](#)

[eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf](#)

[eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf](#)

[eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf](#)

System overview

[Pilot devices - selection aid](#)

-25 °C

Ambient storage temperature - max

80 °C

Ambient storage temperature - min

40 °C

Equipment heat dissipation, current-dependent P_{vid}

0 W

Force for positive opening - min

0 N

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0 W

Opening diameter

22.5 mm

Opening height

0 mm

Operating torque

0.3 Nm

Rated operational current for specified heat dissipation (I_n)

0 A

Static heat dissipation, non-current-dependent P_{vs}

0 W

Switching angle

60 °

Width opening

0 mm

Bezel color

Titanium

Shock resistance

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal
shock 11 ms

Mechanical, According to IEC/EN 60068-2-27

Color

Black

Bezel material

Plastic

Design

With thumb-grip
Classical

Mounting position

As required

Overvoltage category

III

Degree of protection

NEMA 4X, 13

Degree of protection (front side)

IP66

Functions

Stay-put/spring-return function, can be changed with coding
parts M22-XC-Y

Indicator color

Other

Lens type

Round

Lifespan, mechanical

100,000 Operations

Number of switch positions

2

Size

Front diameter: 29.7 mm

Product category

RMQ-Titan